

Let's talk security...

GSM CAR ALARMS

C
A
R
A
L
A
R
M
S
Y
S
T
E
M
S

CA-1202 Athos

The car alarm CA-1202 is designed for professional protection of a car with possibility of transmission of the alarm information to cellular phone or central monitoring station via GSM/GPRS network. It communicates via GSM/GPRS network. Network selection is made automatically by inserting the SIM card.

MODE 1 for cars without original remote control for central locking Main features for this mode:

- Protecting a car with wired and wireless sensors (wireless sensors can also be used to protect the garage where the car is parked).
- Sending of alarm SMS messages to up to 4 phones.
- Dialing and acoustic alarm warning to up to 4 phones.
- Location tracking of the car (using the triangulation feature of the GSM provider)
- Remote immobilization of the car via SMS instruction.
- Remote control of the alarm system and the central locking via SMS instructions as well as by key chain remote controllers.
- Optional - Hands Free calling (receiving of any incoming call and dialing up to four pre-programmed phone numbers)
- Central monitoring of the car when armed (fully supervised GPRS protocol)

MODE 2 for cars with an original remote control for central locking Main features for this mode:

- Remote control of the alarm system via SMS instructions as well as by the original remote control for central locking.
- Sending of alarm SMS messages to up to 4 phones.
- Dialing and acoustic alarm warning to up to 4 phones.
- Location tracking of the car (using the triangulation feature of the GSM provider)
- Remote immobilization of the car via SMS instruction.
- Protecting a car with wired and wireless sensors (wireless sensors can also be used to protect the garage where the car is parked).
- Optional - Hands Free calling (receiving of any incoming call and dialing up to four pre-programmed phone numbers)
- Remote internet alarm access (user and installer levels) via www.GSMLink.cz

MODE 3 GSM pager for cars with an installed car alarm Main features for this mode:

- Sending of alarm SMS messages to up to 4 phones.
- Dialing and acoustic alarm warning to up to 4 phones.
- Location tracking of the car (using the triangulation feature of the GSM provider)
- Central monitoring of the car when armed (fully supervised GPRS protocol)
- Remote immobilization of the car via SMS instructions.
- Remote control of the alarm system and the central locking via SMS instructions.
- Optional Hands-free calling (receiving of any incoming call and dialing up to four pre-programmed phone numbers)
- Remote internet alarm access (user and installer levels) via www.GSMLink.cz

Technical Specifications

- Sending of info SMS messages up to 4 cellular phones
- Dialing of programmed telephone numbers and playing of an audible warning signal
- Communication with the central monitoring station (CMS)
- Remote access via SMS messages or SMS gate
- Immobilization of the car by SMS
- Up to 4 remote controls
- Garage protection using the JA-60 wireless detectors
- Hands free set
- Adjusting the car alarm via web page www.GSMLink.cz
- GSM pager suitable for any car alarm

Technical Specifications

Power supply voltage	12V DC (8-16V)
Current consumption (quiet)	max. 10 mA
Current consumption (transmitting)	1 A
GSM Bands	E-GSM / GPRS 900/1800MHz

Disclaimer: While all efforts are made to maintain accuracy, the technical specifications and graphics may have inaccuracies or typographical errors. Kawach may make improvements and/or changes in any brochure at any time, without notice. The manufacturer may also change the design / specifications of the product at any time. Kawach can not be held responsible for any loss caused by the above information. For latest updates, please contact us and visit our website: www.kawach.com



CE
Certified

Complies with
ETSI EN 300 220
ETSI EN 301 419-1
EN 301 511
ETS 300 683
ENSIEN 301 489-7
EN 60950
ECE 97.01
CE 0081